

FERROLI

TALENT MULTI-POINT WATER HEATER



- High flow rates up to 14 litres/min (3.1 gals/min)
- 24.4 Kw (83,250 Btu/h) output
- Ideal for use with showers
- Total siting flexibility

RELAX...

it's a

Ferrol

INSTANTANEOUS HOT WATER WHENEVER AND WHEREVER YOU NEED IT

For an instantaneous supply of hot water that never runs out, you need Férroli's versatile new Talent gas-fired room sealed multi-point water heater.

With high flow rates of up to 14 litres/min (3.1 gals/min), the highest of any fan-assisted water heater currently available, the Talent is tailor-made for both domestic and commercial applications. And because the Talent heats water instantaneously direct from the cold water mains supply, it is also very economical in operation - you only heat the water you need.

IDEAL FOR SHOWERS

The Talent is fitted with electronic ignition and a fully modulating gas control valve. The latter adjusts output to match the flow rate, ensuring stable water temperatures at all times. This is an important safety consideration particularly where the elderly or children are using hot water or where showers are being supplied and significant temperature fluctuations are unacceptable. Talent is ideal for use with all types of showers because it supplies hot water at a constant mains pressure. It eliminates the need for power showers.



Stockton Close,
Minworth Industrial Park,
Minworth,
Sutton Coldfield,
West Midlands
B76 1DH
Tel: 0121 352 3500
Fax: 0121 352 3505



EASY TO USE CONTROLS

Fitted with an easy-to-use hot water temperature control giving a 45 to 60 degree C range, the Talent also features a useful LED display for instant visual indication of water temperatures.

TOTAL SITING FLEXIBILITY

When it comes to siting flexibility, the Talent really comes into its own. Stylishly designed and compact in size, it will fit unobtrusively into any domestic or commercial situation. Supplied as standard with a 0.75m concentric flue, optional concentric flue lengths

of up to 3m are available. With Férroli's special twin pipe flue options enabling combined flue lengths of up to 20m, the versatile Talent can be installed virtually anywhere, from a kitchen cupboard to the loft. And because it only weighs 33Kg, it can easily be installed by one man.

FÉRROLI - THE COMPANY

Férroli is one of the world's largest manufacturers of heating appliances. All its products are manufactured to the highest European standards and carry the CE approval mark. Férroli is renowned for its quality of manufacturing and reliability in operation and every Férroli appliance carries a comprehensive guarantee.

And once it is installed, you can relax in the knowledge that every Férroli product is supported by an efficient nationwide after sales servicing and spare parts operation.

RELAX... it's a Férroli

TECHNICAL SPECIFICATION - TALENT

Rated Heat Input	Kw	26.8	Btu/h	91,500
Rated Heat Output	Kw	24.4	Btu/h	83,250
Minimum Heat Output	Kw	9.3	Btu/h	31,000

	Natural Gas (G20)	LPG. (G31)
Pilot Injector	38/36 A	0.25 P
Ø Main Injector	2.25 mm	1.40 mm
Ø Gas Pipe Connection	3/4"	3/4"
Quantity of Main Injectors	4	4
Gas Inlet Pressure (working)	20 mbar	37 mbar
Gas Pressure at Main Burners	min	2 mbar
	max	13.7 mbar
Gas Flow		36 mbar
		2.83 m ³ /h
Water Flow Rate		-
		2.07 Kg/h
Water Flow Rate	Δt 25°C	14 l/min
	Δt 35°C	10 l/min
Maximum Pressure	10 bar	
Adjustable Temperature	min	40°C
	max	65°C
Ø Water Connections	1/2"	

DIMENSIONS

Height:	Width:	Depth:	Weight:	Electrical Supply:
700mm	420mm	270mm	33Kg	230/50 V/Hz

TERMS: Férroli pursues a policy of continuous product improvement and reserves the right to alter specifications and design without prior notice.